

SERIES 8000 SLIDING GLASS DOOR

General Information

SERIES 8000 SLIDING GLASS DOOR		
General Information		
WinDoor Standard Finishes AAMA 2603		
White	UC# 97603	Wet White Handle
Bronze	UC# 98316	Black Handle
WinDoor Standard Kynar Finishes AAMA 2605		
Bone White	UC# 43350	Shield White Handle
Bronze	UC# 91252	Black Handle

Fraction	Decimal
1/32	0.031
1/16	0.063
3/32	0.094
1/8	0.125
5/32	0.156
3/16	0.188
7/32	0.219
1/4	0.250
9/32	0.281
5/16	0.313
11/32	0.344
3/8	0.375
13/32	0.406
7/16	0.438
15/32	0.469
1/2	0.500
17/32	0.531
9/16	0.563
19/32	0.594
5/8	0.625
21/32	0.656
11/16	0.688
23/32	0.719
3/4	0.750
25/32	0.781
13/16	0.813
27/32	0.844
7/8	0.875
29/32	0.906
15/16	0.938
31/32	0.969

NS/WS/2T	Panels
XO	AI-BO
OX	BOR-AIR
XX	AI-AOR
XX-Rev	AO-AIR
OXO	DI-AI-BO
OXO-Rev	BOR-AIR-DIR
XOO	AI-BO-DOR
OOX	DO-BOR-AIR
XXXX	AO-EI-AI-AOR
OXXO	BOR-EI-AI-BO
3T	Panels
XXX	AI-C-AOR
XXX-Rev	AO-CR-AIR
XXO	AI-C-BO
OXX	BOR-CR-AIR
XXXXXX	AO-CR-EI-AI-C-AOR
OXXXXO	BOR-CR-EI-AI-C-BO
4T	Panels
XXXX	AI-C-C-AOR
XXXX-Rev	AO-CR-CR-AIR
XXO	AI-C-C-BO
OXXX	BOR-CR-CR-AIR
XXXXXXXX	AO-CR-CR-EI-AI-C-C-AOR
OXXXXXXO	BOR-CR-CR-EI-AI-C-C-BO
2T	Panels
PX-O	AO-Notched Rev.
PX-I	AIR
XP-O	AO-Notched
XP-I	AI
PXX-O	CNI-AOR
PXX-I	COR-AIR
XXP-O	AO-CNIR
XXP-I	AI-CO
PXXP-O	EO-Notched/AO-Notched
PXXP-I	EI-Notched Rev/AI Notched
PXXXXP-O	CNI-EI-AI-CNIR
PXXXXP-I	CO-EOR-AO-COR
3T	Panels
PXXX-O	CNI-C-AOR
PXXX-I	COR-CR-AIR
XXXP-O	AO-CR-CNIR
XXXP-I	AI-C-CO
PXXXXXP-O	CNI-C-EO-AO-CR-CNIR
PXXXXXP-I	COR-CR-EI-AI-C-CO
4T	Panels
PXXXX-O	CNI-C-C-AOR
PXXXX-I	COR-CR-CR-AIR
XXXXP-O	AO-CR-CR-CNIR
XXXXP-I	AI-C-C-CO
PXXXXXXP-O	CNI-C-C-EOR-AO-CR-CR-CNIR
PXXXXXXP-I	COR-CR-CR-EI-AI-C-C-CO

Tracks	Head	Jamb	Sill
NS/WS	6-1/16	5-7/8	6-9/16
2T	4-5/8	4-7/16	5-1/8
3T	7	6-13/16	7-1/2
4T	9-3/8	9-3/16	9-7/8

On 90 Degree Corners:
The Outside Overall Width is equal to the Inside Overall Width plus the Sill Depth

Fastener Locations	End	Center
8000 Non-reinforced	6"	18"
8000 Reinforced	6"	12"

Panel Size Limits	
Non Impact Single Glaze & 1" Insulated	5'0" x 10'0"
Impact Single Glaze & Insulated Impact	4'0" x 10'0"
	5'0" x 8'0"

Pocket Configurations			
A	Inside	Open	Left
B	Inside	Closed	Left
C	Outside	Open	Left
D	Outside	Closed	Left
E	Inside	Open	Right
F	Inside	Closed	Right
G	Outside	Open	Right
H	Outside	Closed	Right

Sill Riser Height	Test Lab Result	Field Results
1.5	6.75 lb	5.5 lb
2.25"	9.0 lb	7.5 lb
3.0"	12.0 lb	10.5 lb
3.5"	15.0 lb	12.5 lb
4.25"	18.0 lb	16.0 lb

Panel Weights	
1/4 8K	9 lbs/sq ft
NI 8K	10 lbs/sq ft
IG INSUL	11 lbs/sq ft