

SERIES 2000 FIXED WINDOW

General Information

SERIES 2000 FIXED WINDOW	
General Information	
WinDoor Standard Finishes AAMA 2603	
White	UC# 97603
Bronze	UC# 98316
WinDoor Standard Kynar Finishes AAMA 2605	
White	UC# 43350
Bronze	UC# 91252

Fraction	Decimal
1/32	0.031
1/16	0.063
3/32	0.094
1/8	0.125
5/32	0.156
3/16	0.188
7/32	0.219
1/4	0.250
9/32	0.281
5/16	0.313
11/32	0.344
3/8	0.375
13/32	0.406
7/16	0.438
15/32	0.469
1/2	0.500
17/32	0.531
9/16	0.563
19/32	0.594
5/8	0.625
21/32	0.656
11/16	0.688
23/32	0.719
3/4	0.750
25/32	0.781
13/16	0.813
27/32	0.844
7/8	0.875
29/32	0.906
15/16	0.938
31/32	0.969

Frames Available	Frame Depth
Flush	3"
5/8" Flange	3"
1-1/2" Fin	3"

Configurations
1-Lite or Colonial Muntin or Specified
* Product can be divided with common post with some limitations
** Radius tops and designers available with some limitations

Frame Sight Line
Sill Jamb and Head
2-3/4"

Minimum Size Limitations	
Minimum outside dimension of any leg or side	9"
Minimum square foot to manufacture	1 sq ft

Tested Sizes – Non-Impact	
4' x 12'	Do Not Exceed Height or Width in Any Size Configuration for Certification
5' x 10'	
6' x 8'	
Tested up to +200psf/-200psf. Pressures dependent on glass type. Please consult factory.	

Tested Sizes – Impact	
4' x 10'	Do Not Exceed Height or Width in Any Size Configuration for Certification
5' x 8'	
Tested up to +150psf/-175psf. Pressures dependent on glass type. Please consult factory.	