

# SERIES 1000 FIXED WINDOW

## General Information

SERIES 1000 FIXED WINDOW	
General Information	
WinDoor Standard Finishes AAMA 2603	
White	UC# 97603
Bronze	UC# 98316

Fraction	Decimal
1/32	0.031
1/16	0.063
3/32	0.094
1/8	0.125
5/32	0.156
3/16	0.188
7/32	0.219
1/4	0.250
9/32	0.281
5/16	0.313
11/32	0.344
3/8	0.375
13/32	0.406
7/16	0.438
15/32	0.469
1/2	0.500
17/32	0.531
9/16	0.563
19/32	0.594
5/8	0.625
21/32	0.656
11/16	0.688
23/32	0.719
3/4	0.750
25/32	0.781
13/16	0.813
27/32	0.844
7/8	0.875
29/32	0.906
15/16	0.938
31/32	0.969

Frames Available	Frame Depth
Flush	3"
5/8" Flange	3"
1-1/2" Fin	3"

Configurations
1-Lite or Colonial Muntin or Specified
* Product can be divided with common post with some limitations
** Radius tops and designers available with some limitations

Frame Sight Line
Sill Jamb and Head 2"

Minimum Size Limitations
Minimum outside dimension of any leg or side 9"
Minimum square foot to manufacture 1 sq ft

Tested Sizes – Non-Impact	
5' x 10' *	Do Not Exceed Height or Width in Any Size Configuration for Certification
6' x 8' **	
*Tested up to +180psf/-240psf. **+200psf/-200psf. Pressures dependent on glass type. Please consult factory.	

Tested Sizes – Impact	
4' x 10'	Do Not Exceed Height or Width in Any Size Configuration for Certification
5' x 8'	
Tested up to +150psf/-175psf. Pressures dependent on glass type. Please consult factory.	